



## GENERAL

The exit signs serve for marking the exit doors. Additionally, some of the signs illuminate the floor in the exit resp. entrance area.

The signs can be operated during normal flight operation with 28 V and in case of emergency situation with 5.8 V.



Some exit signs are combined with pictograms: "No Smoking" and "Fasten Seat Belt." In unlighted condition these pictograms are not visible.

The exit signs are tested to **FAR Parts 23,25,27 and 29.**



### Applications:

- Antonov 140
- BAe 146/200/1000
- Boeing 727/737/747
- CASA 3000
- Challenger 300
- DASH 8
- EH 101
- Fairchild Dornier 328 Jet
- Fokker 70/100
- Global Express
- Gulfstream G4
- Jetstream 41/61
- N250
- Saab 340 1./2./3. Generation
- Saab 2000

## WALL MOUNTED EXIT SIGNS COMBINED WITH PICTOGRAMS

### 2LA 006 639-..



#### Technical Data:

- Dimensions: 228 x 200 x 38 mm (8.976 x 7.874 x 1.496")
- Operating voltage: 5.8 and 28 V DC
- Operating current: 0.77/0.53 A max.
- Incandescent lamps: 8GS 005 438-28, 4,000 h/28 V or 8GS 005 424-05, 5,000 h/5 V
- Mass: 0.75 kg (1.65 lbs) max.

#### Different Variants:\*



...-00

### 2LA 005 106-..



#### Technical Data:

- Dimensions: 228 x 200 x 38 mm (8.976 x 7.874 x 1.496")
- Operating voltage: 5.8 and 28 V DC
- Operating current: 0.71/1.31 A max.
- Incandescent lamps: 8GA 005 425-28, 5,000 h/28 V or 8GS 005 424-05, 5,000 h/5 V
- Mass: 0.68 kg (1.5 lbs) max.

#### Different Variants:\*



...-00

\*Further variants are available on request.

## WALL MOUNTED EXIT SIGNS

### 2LA 005 934-..




#### Technical Data:

- Dimensions: 330.4 x 52.2 x 25 mm (13.01 x 2.06 x 0.98")
- Operating voltage: 5.8 or 28 V DC
- Incandescent lamps:
  - 8GS 005 997-05, 2,000 h/6 V
  - or 8GS 005 453-28, 4,000 h/28 V
- Mass:
  - 0.4 kg (0.882 lbs) max. for -00, -25, -28
  - 0.22 kg (0.485 lbs) max. for -10, -20, -23, -35, -40

#### Different Variants:\*



...-00 (2 circuits, 5.8 V, with floorlight)    ...-10 (1 circuit, 5.8 V, with floorlight)



...-20 (1 circuit, 5.8 V)    ...-23 (russian, 1 circuit, 5.8 V)



...-25 (ukrainian, 2 circuits, 28 V, with floorlight)    ...-28 (2 circuits, 28 V, with floorlight)



...-35 (2 circuit, 5.8 V, with floorlight)    ...-40 (2 circuits, 5.8 V)

The cover lenses (P/N 9EL 403 816-..) of this sign may also be used with a triangular housing (P/N 9BG 403 815-00). The P/N of a blank cover lens is 9EL 403 816-55.


### 2LA 006 952-..




#### Technical Data:

- Dimensions: 240 x 77 x 15 mm (9.449 x 3.031 x 0.591")
- Operating voltage: 5.8 or 28 V DC
- Operating current: 0.88 or 0.46 A max.
- Incandescent lamps:
  - 8GS 005 997-05, 2,000 h/6 V
  - or 8GS 007 009-28, 4,000 h/28 V
- Mass: 0.27 kg (0.60 lbs) max.


#### Different Variants:\*




...-00 (5.8 V)    ...-06 (jap., 5.8 V)




...-10 (28 V)    ...-15 (russian, 5.8 V)



...-20 (5.8 V)    ...-50 (5.8 V)



...-51 (5.8 V)    ...-56 (5.8 V)



...-60 (28 V)    ...-65 (28 V)


### 2LA 004 467-..



#### Technical Data:

- Dimensions: 177.8 x 101.6 x 40 mm (7 x 4 x 1.57")
- Operating voltage: 5.8 or 28 V DC
- Operating current: 0.9 or 0.44 A max.
- Incandescent lamps:
  - 8GS 005 376-06, 6,000 h/6 V
  - or 8GS 005 453-28, 4,000 h/28 V
- Mass: 0.21 kg (0.46 lbs) max.

#### Different Variants:\*



...-07 (5.8 V)    ...-25 (jap., 28 + 5.8 V, with floorlight)

## 2LA 007 344-..



### Technical Data:

- Dimensions: 103.1 x 50.8 x 12 mm (4.059 x 2 x 0.472")
- Operating voltage: 6 or 28 V DC
- Operating current: 0.45/0.140 A max.
- Long-life LED backlights, 30,000 h
- Mass: 0.05 kg (0.11 lbs) max.

### Different Variants:\*


acc. to FAR Part 23, 27 and 29



...-50 (28 V)

...-80 (6 V)

acc. to FAR Part 27



...-30 (ukrainian, 28 V)

...-85 (6 V)


## 2LA 455 399-.., 2LA 455 613-..



### Technical Data:


- Dimensions: 307 x 77 x 25.3 mm (12.087 x 3.031 x 0.996")
- Operating voltage: 5.6 V DC
- Operating current: 0.48 A max.
- LED backlight
- Mass: 0.3 kg (0.66 lbs) max.

### Different Variants:\*



2LA 455 399-00

...-01



2LA 455 613-00

## 700311-.. (TYPE A)



### Technical Data:

- Dimensions: 424.7 x 66.8 mm (16.72" x 2.63")
- Operating voltage: 6 V DC
- Operating current: 1.95 A max.
- Mass: 0.37 kg (0.82 lbs) max.

### Different Variants:\*

- 1 english
- 2 french/english
- 3 spanish/english
- 4 hebrew/english
- 5 portugese/english
- 6 greek/english
- 7 korean/english
- 8 english with arrows
- 9 english with arrows
- 10 arabic/english
- 11 persian/english
- 12 persian/english with arrows
- 13 persian/english with arrows
- 14 chinese/english
- 15 arabic/english with arrows
- 16 arabic/english with arrow
- 17 arabic/english
- 18 english with arrows
- 19 persian/english with arrows
- 20 arabic/english with arrows
- 21 chinese/english
- 22 chinese/english with arrows
- 23 chinese/english with arrows
- 24 chinese/english with arrows
- 25 chinese/english

\*Further variants are available on request.

- 26 french/arabic/english
- 27 arabic/english
- 28 japanese/english
- 29 spanish/english
- 30 urdu/english
- 31 arabic/english
- 32 chinese/english
- 33 chinese/english with arrows
- 34 chinese/english with arrows
- 35 chinese/english with arrows
- 36 arabic/english
- 37 korean/english with arrows
- 38 korean/english with arrows
- 39 korean/english with arrows
- 40 arabic/english
- 41 arabic/english with arrows
- 42 arabic/english with arrows
- 43 arabic/english with arrows
- 44 portugese/english
- 45 arabic/english
- 46 japanese/english
- 47 malaysian/english
- 48 portugese/english

**700312-.. (TYPE B)**



**Technical Data:**

- Dimensions: 340.4 x 83.8 mm (13.40 ± 0.3" x 3.3 ± 0.3")
- Operating current: 1.95 A max.
- Mass: 0.53 kg (1.17 lbs) max.

**Different Variants:\***

- 1 english with arrows
- 2 english
- 3 french/english with arrows
- 4 french/english
- 5 spanish/english with arrows
- 6 spanish/english
- 7 hebrew/english with arrows
- 8 hebrew/english
- 9 portugese/english with arrows
- 10 portugese/english
- 11 greek/english with arrows
- 12 greek/english
- 13 korean/english with arrows
- 14 korean/english
- 15 english
- 16 french/english
- 17 english with sloped arrows
- 18 arabic/english with arrows
- 19 arabic/english
- 20 persian/english
- 21 persian/english with arrows
- 22 english with arrows
- 23 chinese/english
- 24 chinese/english with arrows
- 25 portugese/english with arrows

- 26 arabic/english with arrows
- 27 arabic/english
- 28 english - emergency exit
- 29 chinese/english with arrows
- 30 chinese/english
- 31 french/arabic/english with arrows
- 32 english with sloped arrows
- 33 french/english with sloped arrows
- 34 arabic/english
- 35 french/english with arrows
- 36 arabic/english with arrows
- 37 french/arabic/english with arrows
- 38 arabic/english with arrows
- 39 japanese/english with arrows
- 40 japanese/english
- 41 swahili/english with arrows
- 42 arabic/english
- 43 spanish/english with arrows
- 44 spanish/english
- 45 arabic/english with arrows
- 46 urdu/english with arrows
- 47 urdu/english
- 48 arabic/english with arrows
- 49 arabic/english
- 50 french/arabic/english with arrow
- 51 chinese/english with arrowss
- 52 chinese/english
- 53 japanese/english
- 54 arabic/english with arrows
- 55 arabic/english
- 56 norwegian/english with arrows
- 57 english with arrows
- 58 english - emergency exit
- 59 arabic/english
- 60 arabic/english with arrows
- 61 arabic/english with arrows
- 62 hindi/english with arrows
- 63 french/english with arrows
- 64 arabic/english
- 65 chinese/english with arrows
- 66 portugese/english with arrows
- 67 japanese/english with arrows
- 68 japanese/english

\*Further variants are available on request.

## 702216-... (TYPE C)



### Technical Data:

- Dimensions: Mounting hole to hole  
433.8 x 52.8 mm (17.08" x 2.08")
- Operating current: 1.95 A max.
- Mass: 0.454 kg (1 lbs) max.

### Different Variants:\*

- |                                    |                                    |                                    |
|------------------------------------|------------------------------------|------------------------------------|
| -108 french/english                | -151 english with arrow            | -191 japanese/english with arrows  |
| -109 french/english with arrows    | -152 english with arrow            | -192 japanese/english with arrows  |
| -110 french/english with arrow     | -153 english with arrow            | -193 japanese/english              |
| -111 english with arrows           | -154 portugese/english             | -194 japanese/english with arrow   |
| -113 english                       | -155 portugese/english with arrows | -195 japanese/english with arrow   |
| -114 english with arrow            | -156 portugese/english with arrow  | -197 french/english with arrow     |
| -116 english with arrow            | -158 arabic/english with arrow     | -198 french/english with arrow     |
| -117 english with arrow            | -159 arabic/english with arrow     | -199 french/english with arrows    |
| -121 japanese/english              | -160 japanese/english with arrow   | -200 french/english with arrows    |
| -122 japanese/english with arrows  | -161 japanese/english with arrow   | -201 french/english with arrow     |
| -123 japanese/english with arrow   | -162 japanese/english with arrow   | -202 french/english with arrows    |
| -124 arabic/english                | -168 french/english                | -203 french/english with arrows    |
| -125 arabic/english with arrows    | -169 french/english with arrows    | -204 french/english with arrows    |
| -127 arabic/english with arrows    | -170 french/english with arrow     | -205 japanese/english with arrow   |
| -128 portugese/english             | -171 french/english with arrow     | -206 french/english with arrows    |
| -129 portugese/english with arrows | -172 french/english with arrow     | -207 japanese/english with arrows  |
| -130 portugese/english with arrow  | -173 chinese/english with arrow    | -209 korean/english with arrows    |
| -133 arabic/english                | -174 chinese/english with arrow    | -210 korean/english                |
| -134 arabic/english with arrows    | -175 chinese/english with arrows   | -211 japanese/english with arrow   |
| -135 arabic/english with arrow     | -176 chinese/english               | -212 chinese/english with arrow    |
| -139 japanese/english with arrow   | -177 chinese/english with arrow    | -213 chinese/english with arrows   |
| -140 japanese/english with arrows  | -182 japanese/english with arrow   | -214 portugese/english with arrow  |
| -141 japanese/english              | -183 japanese/english with arrow   | -216 japanese/english with arrow   |
| -142 japanese/english              | -184 chinese/english with arrows   | -217 hebrew/english with arrow     |
| -143 japanese/english with arrow   | -185 chinese/english with arrow    | -218 malaysian/english with arrows |
| -146 malaysian/english with arrows | -186 chinese/english with arrow    | -219 malaysian/english with arrows |
| -147 malaysian/english             | -187 chinese/english with arrow    | -220 arabic/english                |
| -148 malaysian/english with arrow  | -188 chinese/english               | -221 italian/english with arrow    |
| -149 malaysian/english with arrow  | -189 malaysian/english with arrow  |                                    |
| -150 english with arrows           | -190 japanese/english with arrow   |                                    |

\*Further variants are available on request.

## 702409-....



### Technical Data:

- Dim.: 127 x 44.5 x 12.7 mm (5" x 1.75" x 0.5")
- Operating current: 0.35 A max.
- Mass: 0.057 kg (2 oz.)

### Different Variants:\*

- 1001 english
- 1002 english
- 1003 english
- 1004 spanish/english
- 1005 spanish/english
- 1006 spanish/english
- 1007 english/spanish
- 1008 english/spanish
- 1009 english/spanish
- 1010 french/english
- 1011 french/english
- 1012 french/english
- 1013 english/french
- 1014 english/french
- 1015 english/french
- 1016 english/french
- 1017 english/french
- 1018 english/french
- 1019 german/english
- 1020 german/english
- 1021 german/english
- 1022 yugoslav/english
- 1023 yugoslav/english
- 1024 yugoslav/english
- 1025 chinese/english
- 1026 chinese/english
- 1027 chinese/english
- 1028 korean/english
- 1029 korean/english
- 1030 korean/english
- 1031 thai/english
- 1032 thai/english
- 1033 thai/english
- 1034 malay/english
- 1035 malay/english
- 1036 malay/english
- 1037 english/dutch
- 1038 english/dutch
- 1039 english/dutch
- 1040 english/norwegian
- 1041 english/norwegian
- 1042 english/norwegian
- 1043 english/japanese
- 1044 english/japanese
- 1045 dutch/english
- 1046 dutch/english
- 1047 dutch/english
- 1048 japanese/english
- 1049 chinese/english
- 1050 english/greek
- 1051 english/greek
- 1052 english/greek
- 1053 portugese/english
- 1054 english/dane
- 1055 english/dane
- 1056 english/dane
- 1057 chinese/english
- 1058 chinese/english
- 1059 chinese/english
- 1060 arabic/english
- 1061 arabic/english
- 1062 arabic/english
- 1063 bengali/english
- 1064 bengali/english
- 1065 bengali/english
- 1066 arabic/english
- 1067 arabic/english
- 1068 arabic/english
- 1069 devanagari/english
- 1070 devanagari/english
- 1071 devanagari/english
- 1072 hebrew/english
- 1073 hebrew/english
- 1074 hebrew/english
- 1075 ethiopian/english
- 1076 ethiopian/english
- 1077 ethiopian/english
- 1079 portuguese/english
- 1080 no language assigned
- 1081 portuguese/english
- 1082 portuguese/english
- 1083 turkish/english
- 1084 turkish/english
- 1085 turkish/english
- 1086 english
- 1087 english
- 1089 english/icelandic
- 1090 english/icelandic
- 1091 english/icelandic
- 1092 english/swedish
- 1093 english/swedish
- 1094 english/swedish
- 1095 arabic/english
- 1096 arabic/english
- 1097 arabic/english
- 1098 english/bulgarian
- 1099 english/bulgarian
- 1100 english/bulgarian
- 1101 english/japanese
- 1102 greek/english
- 1103 greek/english
- 1104 greek/english
- 1105 hungarian/english
- 1106 hungarian/english
- 1107 hungarian/english
- 1108 english/turkish
- 1109 english/turkish
- 1110 english/turkish
- 1111 korean/english
- 1112 korean/english
- 1113 korean/english
- 1114 polish/english
- 1115 polish/english
- 1116 polish/english
- 1117 english/romanian
- 1118 english/romanian
- 1119 english/romanian
- 1120 russian/english
- 1121 estonian/english
- 1122 estonian/english
- 1123 estonia/english
- 1124 turkman/english
- 1125 uzbek/english
- 1126 arabic/english
- 1127 swahili/english
- 1129 swahili/english
- 1130 swahili/english
- 1131 chinese/english
- 1132 arabic/english
- 1133 hindi/english
- 1134 hindi/english
- 1135 hindi/english
- 1137 english/malaysian
- 1138 russian/english
- 1139 russian/english
- 1141 russian/english
- 1142 english/japanese
- 1143 ukrainian/english
- 1144 ukrainian/english
- 1145 ukrainian/english
- 1146 azerbaijany/english
- 1147 azerbaijany/english
- 1148 azerbaijany/english
- 1149 czech/english
- 1150 czech/english
- 1151 czech/english
- 1152 italian/english
- 1153 swahili/english
- 1154 kazakh/english
- 1155 italian/english
- 1156 italian/english
- 1157 italian/english
- 2001 german/english
- 2002 portuguese/english
- 2003 saudi arabic/english
- 2004 french/english
- 2005 english/japanese
- 2006 japanese/english
- 2007 english
- 2008 english
- 2009 english/japanese
- 2010 kuwait arabic/english
- 2011 kuwait arabic/english
- 2012 japanese/english
- 2013 chinese/english
- 2014 spanish/english
- 2015 arabic/english
- 2016 arabic/english
- 2017 arabic/english
- 2018 spanish/english
- 2019 japanese/english
- 2020 japanese/english
- 2021 chinese/english
- 2022 portuguese/english
- 2023 egyptian/english
- 2024 egyptian/english
- 2025 arabic/english
- 2026 arabic/english
- 2027 french/english
- 2028 french/english
- 2029 german/english
- 2030 german/english
- 2031 polish/english
- 2032 polish/english
- 2033 french/english
- 2034 french/english
- 2037 greek/english
- 2038 greek/english
- 2039 spanish/english
- 2040 spanish/english
- 2041 french/english
- 2042 french/english
- 2043 french/english
- 2044 french/english
- 2046 italian/english
- 2047 italian/english
- 2048 english
- 2049 kazakh/english
- 3001 french/english
- 3002 english
- 3003 arabic/english
- 3004 japanese/english
- 3005 chinese/english
- 3006 spanish/english
- 3010 malay/english
- 3011 chinese/english
- 3013 arabic/english
- 3014 italian/english
- 3015 uzbek/english
- 3016 japanese/english
- 4000 no language assigned

\*Further variants are available on request.

## CEILING MOUNTED EXIT SIGNS

### 2LA 007 459-..



#### Technical Data:

- Dimensions: 420 x 51.9 x 50 mm (16.5 x 2.04 x 1.97")
- Operating voltage: 5.8 and 28 V DC
- Operating current: 1.43/0.71 A max.
- Incandescent lamps:  
8GS 005 453-28, 4,000 h/28 V  
or 8GS 005 376-05, 6,400 h/5.8 V
- Mass: 0.27 kg (0.60 lbs) max.

**Note: Legends on both sides**

#### Different Variants:\*



...00 (indonesian)

### 2LA 005 936-..



#### Technical Data:

- Dimensions: 231 x 82.5 x 40 mm (9.09 x 3.25 x 1.57")
- Operating voltage: 5.8 V DC
- Operating current: 0.81 A max.
- Incandescent lamps: 8GS 005 997-05, 2,000 h/6 V, 2 circuits
- Mass: 0.25 kg (0.55 lbs) max.

**Note: Legends on both sides**

#### Different Variants:\*



...02



...10

### 2LA 006 842-..



#### Technical Data:

- Dimensions: 360 x 50 x 52 mm (14.173 x 1.97 x 2.047")
- Operating voltage: 5.8 or 28 V DC
- Operating current: 0.86 or 0.29 A max.
- Incandescent lamps:  
8GS 005 997-05, 2,000 h/6 V  
or 8GS 006 256-28, 6,000 h/28 V
- Mass: 0.24 kg (0.53 lbs) max.

**Note: Legends on both sides**

#### Different Variants:\*



...00 (5.8 V)



...06 (jap.), (5.8 V)



...10 (5.8 V, printed only on one side)



...15 (28 V, printed only on one side)



...25 (ukrainian, 28 V)



...28 (russian, 28 V)

\*Further variants are available on request.

**Goodrich Hella Aerospace  
Lighting Systems GmbH**  
Bertramstrasse 8  
59557 Lippstadt/Germany  
Tel.: +49 2941 7676-0  
Fax: +49 2941 7676-8432  
Sita: PADHECR

**North American Operations:  
Goodrich Hella Aerospace  
Lighting Systems, Inc.**  
129 Fairfield Street  
Oldsmar, FL 34677  
Tel.: +1 813 891-7100  
Fax: +1 813 855-5572

<http://www.hella.goodrich.com>  
[info@hella.goodrich.com](mailto:info@hella.goodrich.com)

ExitSigns/TA/Aug 2003

The Goodrich name, logotype and symbol are registered trademarks of Goodrich Corporation